



MAIN FEATURES:

- Unitary insulation test at 4KV
- According **EN61558** European Standard (CE)
- All used materials are minimum **Class B** (130°C)
- Non accessible metal parts
- Protection index: **IP-20**
- Encapsulated with epoxy resin
- **DIN Rail** mounting system
- **Other voltages or powers under request**

JESIVA Part nº	RATED POWER	INPUT	OUTPUT	TEMP	SIZES (mm)					WEIGHT
					A	B	C	D	E	
ETCD2301212	12VA	230V	12V / 1.0A	40°C	52	61	53	44	10	350 gr
ETCD2301216	16VA	230V	12V / 1.33A	40°C	58	64	59	50	10	450 gr
ETCD2301224	24VA	230V	12V / 2.0A	40°C	64	67	68	58	10	750 gr
ETCD2301245	45VA	230V	12V / 3.75A	40°C	70	70	74	65	10	1100 gr
ETCD2301264	64VA	230V	12V / 5.33A	40°C	83	77	82	73	10	1400 gr
ETCD2302412	12VA	230V	24V / 0.5A	40°C	52	61	53	44	10	350 gr
ETCD2302416	16VA	230V	24V / 0.66A	40°C	58	64	59	50	10	450 gr
ETCD2302424	24VA	230V	24V / 1.0A	40°C	64	67	68	58	10	750 gr
ETCD2302445	45VA	230V	24V / 1.87A	40°C	70	70	74	65	10	1100 gr
ETCD2302464	64VA	230V	24V / 2.66A	40°C	83	77	82	73	10	1400 gr
ETCD2304812*	12VA	230V	48V / 0.25A	40°C	52	61	53	44	10	350 gr
ETCD2304816*	16VA	230V	48V / 0.33A	40°C	58	64	59	50	10	450 gr
ETCD2304824*	24VA	230V	48V / 0.5A	40°C	64	67	68	58	10	750 gr
ETCD2304845*	45VA	230V	48V / 0.94A	40°C	70	70	74	65	10	1100 gr
ETCD2304864*	64VA	230V	48V / 1.33A	40°C	83	77	82	73	10	1400 gr
ETCD23011512*	12VA	230V	115V / 0.1A	40°C	52	61	53	44	10	350 gr
ETCD23011516*	16VA	230V	115V / 0.14A	40°C	58	64	59	50	10	450 gr
ETCD23011524*	24VA	230V	115V / 0.21A	40°C	64	67	68	58	10	750 gr
ETCD23011545*	45VA	230V	115V / 0.39A	40°C	70	70	74	65	10	1100 gr
ETCD23011564*	64VA	230V	115V / 0.55A	40°C	83	77	82	73	10	1400 gr

DATA SHEET

ETCD DIN Rail Transformers

JESIVA 
transformers

Code:

ETCD230XXX

Date:

Jul 2011

www.JESIVA.com