




Single secondary version

Primary: pins 1 - 5
Secondary: pins 7 - 9



Double secondary version

Primary: pins 1 - 5
Secondary 1: pins 6 - 7
Secondary 2: pins 9 - 10



MAIN FEATURES:

- Unitary insulation test at **5KV**
- According **EN61558** European Standard (CE)
- All used materials are minimum **Class B** (130°C)
- Protection index: **IP00**
- Weight: **45gr**
- **Other voltages or pin-out under request**

JESIVA Part nº	RATED POWER	PRIMARY	SECONDARY	TEMP	Recommended FUSE
E3005.05.1.06	0.5VA	230V	6V / 0.083A	70°C/B	Short-circuit proof
E3005.05.1.07	0.5VA	230V	7.5V / 0.066A	70°C/B	Short-circuit proof
E3005.05.1.09	0.5VA	230V	9V / 0.055A	70°C/B	Short-circuit proof
E3005.05.1.12	0.5VA	230V	12V / 0.041A	70°C/B	Short-circuit proof
E3005.05.1.15	0.5VA	230V	15V / 0.033A	70°C/B	Short-circuit proof
E3005.05.1.18	0.5VA	230V	18V / 0.027A	70°C/B	Short-circuit proof
E3005.05.1.24	0.5VA	230V	24V / 0.020A	70°C/B	Short-circuit proof
E3005.05.2.06	0.5VA	230V	2x6V / 2x0.041A	70°C/B	Short-circuit proof
E3005.05.2.07	0.5VA	230V	2x7.5V / 2x0.033A	70°C/B	Short-circuit proof
E3005.05.2.09	0.5VA	230V	2x9V / 2x0.027A	70°C/B	Short-circuit proof
E3005.05.2.12	0.5VA	230V	2x12V / 2x0.020A	70°C/B	Short-circuit proof
E3005.05.2.15*	0.5VA	230V	2x15V / 2x0.016A	70°C/B	Short-circuit proof
E3005.05.2.18*	0.5VA	230V	2x18V / 2x0.013A	70°C/B	Short-circuit proof
E3005.05.2.24*	0.5VA	230V	2x24V / 2x0.010A	70°C/B	Short-circuit proof

DATA SHEET

EI30/5

Encapsulated transformer

JESIVA 
transformers

Code:

E3005.05.X.XX

Date:

Dec 2011

www.JESIVA.com