




Single secondary version

Primary: pins 1 - 5
Secondary: pins 7 - 9



Double secondary version

Primary: pins 1 - 5
Secondary 1: pins 6 - 7
Secondary 2: pins 9 - 10



MAIN FEATURES:

- Unitary insulation test at 5KV
- According EN 61558 European Standard (CE)
- All used materials are minimum Class B (130°C)
- Protection index: IP00
- Weight: 75gr
- Other voltages or pin-out under request

JESIVA Part nº	RATED POWER	PRIMARY	SECONDARY	TEMP	Recommended FUSE
E3010.15.1.06	1.5VA	230V	6V / 0.25A	70°C/B	Short-circuit proof
E3010.15.1.07	1.5VA	230V	7.5V / 0.20A	70°C/B	Short-circuit proof
E3010.15.1.09	1.5VA	230V	9V / 0.166A	70°C/B	Short-circuit proof
E3010.15.1.12	1.5VA	230V	12V / 0.125A	70°C/B	Short-circuit proof
E3010.15.1.15	1.5VA	230V	15V / 0.10A	70°C/B	Short-circuit proof
E3010.15.1.18	1.5VA	230V	18V / 0.083A	70°C/B	Short-circuit proof
E3010.15.1.24	1.5VA	230V	24V / 0.062A	70°C/B	Short-circuit proof
E3010.15.2.06	1.5VA	230V	2x6V / 2x0.125A	70°C/B	Short-circuit proof
E3010.15.2.07	1.5VA	230V	2x7.5V / 2x0.10A	70°C/B	Short-circuit proof
E3010.15.2.09	1.5VA	230V	2x9V / 2x0.083A	70°C/B	Short-circuit proof
E3010.15.2.12	1.5VA	230V	2x12V / 2x0.062A	70°C/B	Short-circuit proof
E3010.15.2.15	1.5VA	230V	2x15V / 2x0.050A	70°C/B	Short-circuit proof
E3010.15.2.18*	1.5VA	230V	2x18V / 2x0.042A	70°C/B	Short-circuit proof
E3010.15.2.24*	1.5VA	230V	2x24V / 2x0.031A	70°C/B	Short-circuit proof

DATA SHEET

EI30/10.5

Encapsulated transformer

JESIVA 
transformers

Code:

E3010.15.X.XX

Date:

Dic 2011

www.JESIVA.com