




#### Single secondary version

Primary: pins 1 - 5  
Secondary: pins 7 - 9



#### Double secondary version

Primary: pins 1 - 5  
Secondary 1: pins 6 - 7  
Secondary 2: pins 9 - 10



### MAIN FEATURES:

- Unitary insulation test at 5KV
- According **EN61558** European Standard (CE)
- All used materials are minimum **Class B** ( $130^{\circ}\text{C}$ )
- Protection index: **IP00**
- Weight: **75gr**
- **Other voltages or pin-out under request**

JESIVA Part nº	RATED POWER	PRIMARY	SECONDARY	TEMP	Recommended FUSE
E3010.18.1.06	1.8VA	230V	6V / 0.30A	40°C/B	Short-circuit proof
E3010.18.1.07	1.8VA	230V	7.5V / 0.24A	40°C/B	Short-circuit proof
E3010.18.1.09	1.8VA	230V	9V / 0.20A	40°C/B	Short-circuit proof
E3010.18.1.12	1.8VA	230V	12V / 0.15A	40°C/B	Short-circuit proof
E3010.18.1.15	1.8VA	230V	15V / 0.12A	40°C/B	Short-circuit proof
E3010.18.1.18	1.8VA	230V	18V / 0.10A	40°C/B	Short-circuit proof
E3010.18.1.24	1.8VA	230V	24V / 0.075A	40°C/B	Short-circuit proof
E3010.18.2.06	1.8VA	230V	2x6V / 2x0.15A	40°C/B	Short-circuit proof
E3010.18.2.07	1.8VA	230V	2x7.5V / 2x0.12A	40°C/B	Short-circuit proof
E3010.18.2.09	1.8VA	230V	2x9V / 2x0.10A	40°C/B	Short-circuit proof
E3010.18.2.12	1.8VA	230V	2x12V / 2x0.075A	40°C/B	Short-circuit proof
E3010.18.2.15	1.8VA	230V	2x15V / 2x0.060A	40°C/B	Short-circuit proof
E3010.18.2.18*	1.8VA	230V	2x18V / 2x0.050A	40°C/B	Short-circuit proof
E3010.18.2.24*	1.8VA	230V	2x24V / 2x0.037A	40°C/B	Short-circuit proof

# DATA SHEET

## EI30/10.5

Encapsulated transformer

**JESIVA**   
transformers

Code:

E3010.18.X.XX

Date:

Dec 2011

[www.JESIVA.com](http://www.JESIVA.com)