




### Single secondary version

Primary: pins 1 - 5  
Secondary: pins 7 - 9



### Double secondary version

Primary: pins 1 - 5  
Secondary 1: pins 6 - 7  
Secondary 2: pins 9 - 10



## MAIN FEATURES:

- Unitary insulation test at **5KV**
- According **EN61558** European Standard (CE)
- All used materials are minimum **Class B** ( $130^{\circ}\text{C}$ )
- Protection index: **IP00**
- Weight: **115gr**
- **Other voltages or pin-out under request**

JESIVA Part nº	RATED POWER	PRIMARY	SECONDARY	TEMP	Recommended FUSE
E3018.28.1.06	2.8VA	230V	6V / 0.46A	40°C/B	Short-circuit proof
E3018.28.1.07	2.8VA	230V	7.5V / 0.37A	40°C/B	Short-circuit proof
E3018.28.1.09	2.8VA	230V	9V / 0.31A	40°C/B	Short-circuit proof
E3018.28.1.12	2.8VA	230V	12V / 0.23A	40°C/B	Short-circuit proof
E3018.28.1.15	2.8VA	230V	15V / 0.18A	40°C/B	Short-circuit proof
E3018.28.1.18	2.8VA	230V	18V / 0.15A	40°C/B	Short-circuit proof
E3018.28.1.24	2.8VA	230V	24V / 0.11A	40°C/B	Short-circuit proof
E3018.28.2.06	2.8VA	230V	2x6V / 2x0.23A	40°C/B	Short-circuit proof
E3018.28.2.07	2.8VA	230V	2x7.5V / 2x0.18A	40°C/B	Short-circuit proof
E3018.28.2.09	2.8VA	230V	2x9V / 2x0.15A	40°C/B	Short-circuit proof
E3018.28.2.12	2.8VA	230V	2x12V / 2x0.11A	40°C/B	Short-circuit proof
E3018.28.2.15	2.8VA	230V	2x15V / 2x0.093A	40°C/B	Short-circuit proof
E3018.28.2.18*	2.8VA	230V	2x18V / 2x0.077A	40°C/B	Short-circuit proof
E3018.28.2.24*	2.8VA	230V	2x24V / 2x0.058A	40°C/B	Short-circuit proof

# DATA SHEET

## EI30/18

Encapsulated transformer

**JESIVA**   
transformers

Code:

E3018.28.X.XX

Date:

Dec 2011

[www.JESIVA.com](http://www.JESIVA.com)