




Single secondary version

Primary: pins 1 - 5
Secondary: pins 7 - 9



Double secondary version

Primary: pins 1 - 5
Secondary 1: pins 6 - 7
Secondary 2: pins 9 - 10



MAIN FEATURES:

- Unitary insulation test at **5KV**
- According **EN61558** European Standard (CE)
- All used materials are minimum **Class B** (130°C)
- Protection index: **IP00**
- Weight: **200gr**
- **Other voltages or pin-out under request**

JESIVA Part nº	RATED POWER	PRIMARY	SECONDARY	TEMP	Recommended FUSE
E4214.50.1.06	5VA	230V	6V / 0.83A	70°C/B	Prim. 40mA/T
E4214.50.1.07	5VA	230V	7.5V / 0.66A	70°C/B	Prim. 40mA/T
E4214.50.1.09	5VA	230V	9V / 0.55A	70°C/B	Prim. 40mA/T
E4214.50.1.12	5VA	230V	12V / 0.41A	70°C/B	Prim. 40mA/T
E4214.50.1.15	5VA	230V	15V / 0.33A	70°C/B	Prim. 40mA/T
E4214.50.1.18	5VA	230V	18V / 0.27A	70°C/B	Prim. 40mA/T
E4214.50.1.24	5VA	230V	24V / 0.20A	70°C/B	Prim. 40mA/T
E4214.50.2.06	5VA	230V	2x6V / 2x0.41A	70°C/B	Sec. 2x500mA/F
E4214.50.2.07	5VA	230V	2x7.5V / 2x0.33A	70°C/B	Sec. 2x400mA/F
E4214.50.2.09	5VA	230V	2x9V / 2x0.27A	70°C/B	Sec. 2x315mA/F
E4214.50.2.12	5VA	230V	2x12V / 2x0.20A	70°C/B	Sec. 2x250mA/F
E4214.50.2.15	5VA	230V	2x15V / 2x0.16A	70°C/B	Sec. 2x200mA/F
E4214.50.2.18	5VA	230V	2x18V / 2x0.13A	70°C/B	Sec. 2x160mA/F
E4214.50.2.24*	5VA	230V	2x24V / 2x0.10A	70°C/B	Sec. 2x125mA/F

DATA SHEET

EI42/14.5

Encapsulated transformer



Code:

E4214.50.X.XX

Date:

Dec 2011

www.JESIVA.com