




Single secondary version
 Primary: pins 1 - 8
 Secondary: pins 10 - 15



Double secondary version
 Primary: pins 1 - 8
 Secondary 1: pins 9 - 10
 Secondary 2: pins 15 - 16



MAIN FEATURES

- Unitary insulation test at **5KV**
- According **EN61558** European Standard (CE)
- All used materials are minimum **Class B** (130°C)
- Protection index: **IP00**
- Weight: **1100gr**
- **Other voltages or pin-out under request**

JESIVA Part nº	RATED POWER	PRIMARY	SECONDARY	TEMP	Recommended FUSE
E6635.45.1.06	45VA	230V	6V / 7.5A	40°C/B	Prim.250mA/T
E6635.45.1.07	45VA	230V	7.5V / 6A	40°C/B	Prim.250mA/T
E6635.45.1.09	45VA	230V	9V / 5A	40°C/B	Prim.250mA/T
E6635.45.1.12	45VA	230V	12V / 3.75A	40°C/B	Prim.250mA/T
E6635.45.1.15	45VA	230V	15V / 3A	40°C/B	Prim.250mA/T
E6635.45.1.18	45VA	230V	18V / 2.5A	40°C/B	Prim.250mA/T
E6635.45.1.24	45VA	230V	24V / 1.87A	40°C/B	Prim.250mA/T
E6635.45.2.06	45VA	230V	2x6V / 2x3.75A	40°C/B	Sec.2x4A/F
E6635.45.2.07	45VA	230V	2x7.5V / 2x3A	40°C/B	Sec.2x3.15A/F
E6635.45.2.09	45VA	230V	2x9V / 2x2.5A	40°C/B	Sec.2x2.5A/F
E6635.45.2.12	45VA	230V	2x12V / 2x1.87A	40°C/B	Sec.2x2A/F
E6635.45.2.15	45VA	230V	2x15V / 2x1.5A	40°C/B	Sec.2x1.65A/F
E6635.45.2.18	45VA	230V	2x18V / 2x1.25A	40°C/B	Sec.2x1.25/F
E6635.45.2.24*	45VA	230V	2x24V / 2x0.93A	40°C/B	Sec.2x1A/F

DATA SHEET

EI66/35

Encapsulated transformer

JESIVA 
transformers

Code:

E6635.45.X.XX

Date:

Dec 2011

www.JESIVA.com