



General tolerance: $\pm 0.5\text{mm}$




* All sizes in mm.


Conexión Primario / Primary Connections

(Ejemplo / Example)


Esquema
Circuit arrangement
2x115V



Conexión Serie
Serial connection
230V




Conexión Paralelo
Parallel connection
115V




Conexión Secundario / Secondary Connections

(Ejemplo / Example: U3921.30.2.15)



Esquema
Circuit arrangement
2x15V - 2x1A



Conexión Serie
Serial connection
30V - 1A



Conexión Paralelo
Parallel connection
15V - 2A



MAIN FEATURES:

- Unitary insulation test at **5KV**
- According **EN61558** European Standard (CE)
- All used materials are minimum **Class B** (130°C)
- Protection index: **IP00**
- Weight: **560gr**
- Other voltages or pin-out** under request

PART Nº	RATED POWER	PRIMARY	SECONDARY	TEMP	Recommended FUSE
U3921.30.2.06	30VA	2x115V	2x6V / 2x2.50A	50°C/B	Sec. 2x2.5A/F
U3921.30.2.07	30VA	2x115V	2x7.5V / 2x2.00A	50°C/B	Sec. 2x2A/F
U3921.30.2.09	30VA	2x115V	2x9V / 2x1.66A	50°C/B	Sec. 2x2A/F
U3921.30.2.12	30VA	2x115V	2x12V / 2x1.25A	50°C/B	Sec. 2x1.25A/F
U3921.30.2.15	30VA	2x115V	2x15V / 2x1.00A	50°C/B	Sec. 2x1A/F
U3921.30.2.18	30VA	2x115V	2x18V / 2x0.83A	50°C/B	Sec. 2x1A/F
U3921.30.2.24*	30VA	2x115V	2x24V / 2x0.62A	50°C/B	Sec. 2x630mA/F

DATA SHEET

UI39/21

"Low Profile" encapsulated transformer

JESIVA transformers

Code:

U3921.30.2.XX

Date:

Dec 2011

www.JESIVA.com