


**NOTE:**

- |   |  |
|---|--|
| 1 TOLERANCES UNLESS OTHERWISE SPECIFIED: ±0.25    | 6 FLUID SPECIFICATION:<br>MULTIPLEX LEVEL -- STATIC                            |
| 2 ALL DIMENSION ARE IN mm                         | DRIVING VOLTAGE (TOP) -- 5.0V  |
| 3 GLASS THICKNESS:<br>FRONT -- 1.1<br>BACK -- 1.1 | OPERATING TEMPERATURE: -30 °C TO 80 °C<br>STORAGE TEMPERATURE: -40 °C TO 90 °C |
| 4 VIEWING ANGLE: 6 O'CLOCK                        | 7 CONNECTOR: PIN   |
| 5 POLARIZER: TRANSMISSIVE/POSITIVE                | 8 TN   |





 <b>DKE</b> 东方科脉		<small>液晶显示器件制造 / LCD Displayed Manufacture</small>	
DESIGN MODEL		DKE818	
VAR.	A	DATE	2007.09.07
CUSTOMER MODEL		APPROVED BY	
		CHECKED BY	
PAGE 1/2		DRAWN BY	SY ZHAO

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33
COM1	COM1	7G	7E	7D	7C	8G	8E	8D	8C	S1	9G	9E	9D	13A	13F	13G	13E	13D	13C	13B	9C	DP13	DP9	14E	14D	14C	DP14	15E	15D	15C	DP15	16E	

PIN	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65
COM1	16D	16C	16G	16B	16A	16F	15B	15A	15F	15G	14G	14B	14A	14F	10G	10E	10D	10C	DP10	11E	11D	11C	DP11	11G	12E	12D	12C	12G	12B	12A	COM1	

PIN	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97
COM1	COM1	12F	6D	6C	6G	6B	6A	6F	6E	DP5	11B	5D	5C	5B	5A	5F	5G	5E	DP4	11A	11F	4C	4B	4A	4F	4G	4E	4D	10B	DP3	10A	

PIN	98	99	100	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120	121	122	123	124	125	126	127	128	129	130
COM1	10F	3C	3B	3A	3F	3G	3E	3D	9B	9A	9F	2C	2B	2A	2F	2G	2E	2D	8B	8A	8F	1C	1B	1A	1F	1G	1E	1D	7B	7A	7F	COM1	

 <b>DKE 东方科脉</b> <small>液晶显示器专业制造商 / LCD Experienced Manufacturer</small>			
<b>DESIGN MODEL</b>		<b>DKE818</b>	
<b>VAR.</b>	<b>A</b>	<b>DATE</b>	<b>2007.09.07</b>
<b>CUSTOMER MODEL</b>		<b>APPROVED BY</b>	
		<b>CHECKED BY</b>	
<b>PAGE 2/2</b>		<b>DRAWN BY</b>	<b>SY ZHAO</b>