


PIN	Symbol
1	Vied+(NC)
2	Vied+(NC)
3	Vied-(NC)
4	Vied-(NC)
5	GND
6	Vcom
7	DIG0
8	W0R0
9	DE
10	VS
11	HS
12	B7
13	R6
14	B5
15	B4
16	B3
17	B2
18	B1
19	B0
20	G7
21	G6
22	G5
23	G4
24	G3
25	G2
26	G1
27	G0
28	R7
29	R6
30	R5
31	R4
32	B3
33	B2
34	R1
35	R0
36	GND
37	DCLK
38	GND
39	L/R
40	U/D
41	VGH
42	VGL
43	Avdd
44	RESET
45	NC
46	Vcom
47	DITHB
48	GND
49	NC
50	NC

Pin#	TPDefinition
1	XL
2	YD
3	XR
4	YU



NOTES:

- DISPLAY TYPE: 7.0" TFT/TRANSMISSIVE RoHS
- OPERATING VOLTAGE: 3.0~3.2V
- OPERATING TEMPERATURE: -20°C~+70°C
- STORAGE TEMPERATURE: -30°C~+80°C
- LCM BRIGHTNESS: 300cd/m2(typ); Uniformity: 80%
- VIEWING DIRECTION: 6:00
- DRIVE IC: ILI6122&ILI5960
- CONNECTOR: FPC
- BACKLIGHT: LED (18 DIES, VF=9.6V, IF=120mA/LED)
- CUSTOMER'S PART ID: BLAZE STANDARD PRODUCT

BLAZE Blaze Display Technology Co.,Ltd.

DESIGNED BY: BDT-23	BDT-T7050-01-SERIES	VERSION: 1.0
CHECKED BY: BDT-09		PAGE 1 OF 1
APPROVED BY: BDT-05		UNIT: mm
Website: http://www.blazedisplay.com		DATE: 2015-12-30