



U74HCT4066

CMOS IC


QUAD BILATERAL SWITCH

DESCRIPTION

The UTC **U74HCT4066** consists of four independent analog switches. Each switch has an Enable input (nE) which is active HIGH to decide the switch status.

FEATURES

- *Operation voltage range: 4.5V~5.5V
- *Very low "ON" resistance: 50Ω(Typ.)@V_{CC}=4.5V




ORDERING INFORMATION


| Ordering Number | Package | Packing |
|-------------------|----------|-----------|
| U74HCT4066G-P14-R | TSSOP-14 | Tape Reel |
| U74HCT4066G-S14-R | SOP-14 | Tape Reel |

| | |
|--------------------------|--|
| <p>U74HCT4066G-P14-R</p> | <p>(1) R: Tape Reel (2) P14: TSSOP-14, S14: SOP-14 (3) G: Halogen Free and Lead Free</p> |
|--------------------------|--|

MARKING



■ PIN CONFIGURATION




■ FUNCTION TABLE

| INPUTS(nE) | SWITCH |
|------------|--------|
| H | ON |
| L | OFF |

Note: H: High voltage level; L: Low voltage level.

■ LOGIC DIAGRAM



■ ABSOLUTE MAXIMUM RATING (T_A=25°C, unless otherwise specified)

| PARAMETER | | SYMBOL | RATINGS | UNIT |
|----------------------|----------|------------------|------------|-------|
| Supply Voltage | | V _{CC} | -0.5 ~ +11 | V |
| Input Diode Current | | I _{IK} | ±20 | mA |
| Switch Diode Current | | I _{SK} | ±20 | mA |
| Switch Current | | I _S | ±25 | mA |
| VCC or GND Current | | I _{CC} | ±50 | mA |
| Power Dissipation | | P _D | 500 | mW |
| Derate above 60°C | TSSOP-14 | | 5.5 | mW/°C |
| Derate above 70°C | SOP-14 | | 8 | mW/°C |
| Storage Temperature | | T _{STG} | -65 ~ +150 | °C |

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS (T_A=25°C, unless otherwise specified)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|------------------------------------|---------------------------------|---------------------|-----|-----|-----------------|------|
| Supply Voltage | V _{CC} | | 4.5 | 5.0 | 5.5 | V |
| Input Voltage | V _{IN} | | GND | | V _{CC} | V |
| Switch Voltage | V _S | | GND | | V _{CC} | V |
| Input Transition Rise or Fall Rate | t _R , t _F | V _{CC} =2V | | 6 | 500 | ns |
| Operating Temperature | T _A | | -40 | | 85 | °C |

■ ELECTRICAL CHARACTERISTICS (T_A=25°C, unless otherwise specified)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|---|----------------------|--|----------------------------------|-----|------|------|
| High-Level Input Voltage | V _{IH} | V _{CC} =4.5V to 5.5V | 2 | | | V |
| Low-Level Input Voltage | V _{IL} | V _{CC} =4.5V to 5.5V | | | 0.8 | V |
| Input Leakage Current | I _{I(LEAK)} | V _{CC} =5.5V, V _{IN} =V _{CC} or GND | | | ±1.0 | μA |
| current per channel | OFF-state | V _{CC} =5.5V, V _{IN} =V _{IH} or V _{IL} , V _S =V _{CC} -GND | | | ±1.0 | μA |
| | ON-state | | | | ±1.0 | μA |
| Quiescent Supply Current | I _Q | V _{CC} =4.5V to 5.5V, V _{IN} =V _{IS} =V _{OS} =V _{CC} or GND | | | 20 | μA |
| Additional Quiescent Supply Current | Δ I _Q | V _{CC} =4.5V to 5.5V, V _{IN} =V _{CC} -2.1V, Other inputs at V _{CC} or GND | | 100 | 450 | μA |
| ON-resistance | Peak | V _{IN} =V _{IH} or V _{IL} , V _{IS} =V _{CC} to GND, V _{CC} =4.5V, I _S =1mA | | 54 | 118 | Ω |
| | Rail | V _{IN} =V _{IH} or V _{IL} , V _{CC} =4.5V, I _S =1mA | V _{IS} =GND | 35 | 95 | Ω |
| | | | V _{IS} =V _{CC} | 42 | 106 | Ω |
| Maximum variation of ON-resistance between any two channels | ΔR _{ON} | V _{IN} =V _{IH} or V _{IL} , V _{IS} =V _{CC} to GND, V _{CC} =4.5V | | 5 | | Ω |

■ DYNAMIC CHARACTERISTICS (T_A=25°C, GND=0V; t_R=t_F=6ns; C_L=50pF)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|------------------------------------|---|-----|------|-----|------|
| Propagation Delay From V _{IS} to V _{OS} | t _{PHL} /t _{PLH} | V _{CC} =4.5V, R _L =∞ | | 3 | 15 | ns |
| Turn-ON Time from nE to V _{OS} | t _{PZH} /t _{PZL} | V _{CC} =4.5V, R _L =1KΩ | | 12 | 30 | ns |
| Turn-OFF Time from nE to V _{OS} | t _{PHZ} /t _{PLZ} | V _{CC} =4.5V, R _L =1KΩ | | 20 | 44 | ns |
| Sine-Wave Distortion | THD | V _{CC} =4.5V, V _{IS(P-P)} =4V, f=1kHz, R _L =10k | | 0.04 | | % |
| Switch OFF Signal Feed-Through (Note 1) | α _{OFF} | V _{CC} =4.5V, R _L =600Ω, f=1MHz | | -50 | | dB |
| Crosstalk Between any two Switches (Note 1) | α _{CT(S)} | V _{CC} =4.5V, R _L =600Ω, f=1MHz | | -60 | | dB |
| Crosstalk Voltage between any input to any Switch (Peak-to-Peak Value) | V _(P-P) | V _{CC} =4.5V, R _L =600Ω, f=1MHz | | 110 | | mV |


■ DYNAMIC CHARACTERISTICS(Cont.)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|-----------|---------------------------------------|-----|-----|-----|------|
| Minimum Frequency Response(-3dB) (Note 2) | f_{MAX} | $V_{CC}=4.5V, R_L=50\Omega, C_L=10pF$ | | 180 | | MHz |
| maximum switch capacitance | C_S | | | 8 | | pF |


Notes: 1. Adjust input voltage V_{IS} is 0dbm level (0dbm=1mW into 600 Ω)
 2. Adjust input voltage V_{IS} is 0dbm level at V_{OS} for 1MHz (0dbm=1mW into 50 Ω)

■ TEST CIRCUIT AND WAVEFORMS


Test circuit for measuring ON-resistance (Ron)




Test circuit for measuring OFF-state current




Test circuit for measuring ON-state current




■ TEST CIRCUIT AND WAVEFORMS(Cont.)



| | S | V _{IN} |
|------------------------------------|-----------------|-----------------|
| t _{PLH} /t _{PHL} | OPEN | |
| t _{PHZ} /t _{PZH} | GND | V _{CC} |
| t _{PLZ} /t _{PZL} | V _{CC} | GND |



PROPAGATION DELAY TIMES



ENABLE AND DISABLE TIMES

Note: 1. C_L includes probe and jig capacitance.
 Note: 2. PRR ≤ 1MHz, Z_o = 50Ω, t_R ≤ 6ns, t_F ≤ 6ns.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.