

Specification

CUN06A1B

| SVC | | Customer |
|-------|----------|----------|
| Drawn | Approval | Approval |
| | | |

[Contents]


- 1. Description**
- 2. Outline dimensions**
- 3. Characteristics of CUN06A1B**
- 4. Characteristic diagrams**
- 5. Binning & Labeling**
- 6. Reel packing**
- 7. Recommended solder pad**
- 8. Reflow Soldering profile**
- 9. Reliability**
- 10. Precaution for use**
- 11. Revision history**

CUN06A1B

Description

High power UV LED series are designed for high current operation and high power output applications.

It incorporates state of the art SMD design and low thermal resistant material. Z5 NUV LED is ideal UV light source for curing, printing, and detecting applications.



CUN06A1B


Features

- Super high power output
- Designed for high current operation
- Low thermal resistance
- SMT solderable
- Lead Free product
- RoHS compliant

Applications

- UV Curing
- Printing
- Coating
- Adhesive
- Counterfeit Detection/ Security
- UV Torch
- Fluorescence Photography
- Dental Curing
- Crime Inspection
- Oil leak Detection

Outline dimensions



Notes :

- [1] All dimensions are in millimeters.
- [2] Scale : none
- [3] Undefined tolerance is $\pm 0.2\text{mm}$

Characteristics of CUN06A1B

1-1 Electro-Optical characteristics at 500mA

(T_a=25℃, RH=30%)

| Parameter | Symbol | Value | Unit |
|--------------------------------|---------------------------------|-------|------|
| Peak wavelength ^[1] | λ_p | 405 | nm |
| Radiant Flux ^[2] | Φ_e ^[3] | 960 | mW |
| Forward Voltage ^[4] | V _F | 3.5 | V |
| Spectrum Half Width | $\Delta \lambda$ | 15 | nm |
| View Angle | 2 $\Theta_{1/2}$ | 120 | deg. |
| Thermal resistance | R θ_{j-b} ^[5] | 9 | ℃ /W |

1-2 Absolute Maximum Ratings


| Parameter | Symbol | Value | Unit |
|-----------------------|------------------|------------|------|
| Forward Current | I _F | 700 | mA |
| Junction Temperature | T _j | 125 | ℃ |
| Operating Temperature | T _{opr} | -10 ~ +85 | ℃ |
| Storage Temperature | T _{stg} | -40 ~ +100 | ℃ |

Notes :


1. Peak Wavelength Measurement tolerance : ±3nm
2. Radiant Flux Measurement tolerance : ± 10%
3. Φ_e is the Total Radiant Flux as measured with an integrated sphere.
4. Forward Voltage Measurement tolerance : ±3%
5. R θ_{j-b} is the thermal resistance between chip junction to PCB board bottom.
The PCB is made of aluminium and the size of PCB is 2.5mm by 2.5mm

Characteristic Diagrams


1. Relative Spectral Power Distribution




2. Forward Current VS Forward Voltage




3. Relative Radiant Flux VS Forward Current




4. Peak Wavelength VS Forward Current




5. Relative Radiant Flux VS Ambient Temperature




6. Peak Wavelength VS Ambient Temperature




7. Forward Voltage VS Ambient Temperature



8. Radiation pattern



9. Allowable Forward Current VS Ambient Temperature



Binning & Labeling

1. Binning Structure

Y₁Y₂Y₃Y₄Y₅

(I_F=500mA)

| Part Number | Y ₁ Y ₂ | | | Y ₃ Y ₄ | | | Y ₅ | | |
|-------------|-------------------------------|-----|-----|-------------------------------|------|------|----------------|-----|-----|
| | Wp [nm] | | | Radiant Flux [mW] | | | Vf [V] | | |
| | BIN | MIN | MAX | BIN | MIN | MAX | BIN | MIN | MAX |
| CUN06A1B | p1 | 400 | 405 | J4 | 760 | 840 | a | 3.0 | 3.4 |
| | | | | J5 | 840 | 920 | b | 3.4 | 3.8 |
| | | | | K1 | 920 | 1000 | c | 3.8 | 4.2 |
| | p2 | 405 | 410 | K2 | 1000 | 1100 | d | 4.2 | 4.6 |
| | | | | K3 | 1100 | 1210 | | | |
| | | | | K4 | 1210 | 1330 | | | |

2. Rank

Y₁Y₂Y₃Y₄Y₅

- Y₁Y₂ : Peak Wavelength [nm]
- Y₃Y₄ : Radiant Flux [mW]
- Y₅ : Forward Voltage [V]

Notes :

1. Peak Wavelength Measurement tolerance : ±3nm
2. Radiant Flux Measurement tolerance : ± 10%
3. Forward Voltage Measurement tolerance : ±3%

RANK :

$$Y_1 Y_2 Y_3 Y_4 Y_5$$


QUANTITY : 500



LOT NUMBER : XXXXXXXXXXXX-XXX-XXX-XXXXXXXX




SOC PART NUMBER : X₁X₂X₃X₄X₅X₆X₇X₈



$$X_1 X_2 X_3 X_4 X_5 X_6 X_7 X_8$$


| X ₁ | | X ₂ | | X ₃ X ₄ | | X ₅ | | X ₆ | | X ₇ | | X ₈ | |
|----------------|---|----------------|---|-------------------------------|----|----------------|---|----------------|---|----------------|---|----------------|---|
| Company | | Product Line | | Wavelength | | PKG Series | | Lens Type | | Chip Q'ty | | Ver | |
| SVC | C | UV | U | Near 395 | N9 | Z5 | 6 | Dome-Wide | A | 1 | 1 | ver0 | A |
| | | | | | | | | | | | | ver1 | B |

Reel Packaging




Recommended solder pad



Notes :

- [1] All dimensions are in millimeters.
- [2] Scale : none
- [3] This drawing without tolerances is for reference only

Reflow Soldering Profile



* Caution

1. Reflow soldering should not be done more than one time.
2. Repairs should not be done after the LEDs have been soldered. When repair is unavoidable, suitable tools must be used.
3. Die slug is to be soldered.
4. When soldering, do not put stress on the LEDs during heating.
5. After soldering, do not warp the circuit board.
6. Recommend to use a convection type reflow machine with 7 ~ 8 zones.

Reliability

1. Relative Spectral Power Distribution

| Test Item | Test Condition | Note | # Failed /Tested |
|-----------------------------|---|----------------------------------|------------------|
| High Temp. Operational Life | Ta=85℃, IF=500mA | 1000hrs | 0/5 |
| Room Temp. Operational Life | Ta=25℃, IF=500mA | 1000hrs | 0/5 |
| Thermal shock | Ta max=120℃, Ta min=-40℃ 30min dwell/transfer time : 10sec, 1 cycle=1hr | 200 cycles | 0/22 |
| Resistance to Soldering | Temp=260±5℃, Time : 10±1 sec | 1 time | 0/10 |
| Solderability | Temp=260±5℃, 95% Coverage | 1 time | 0/10 |
| ESD | R=1.5kΩ, C=100pF Voltage level=2kV | 3 times Negative /positive | 0/22 |

2. Failure Criteria

| Parameter | Symbol | Test Conditions | Max. or Min. allowable shift value |
|-----------------|----------|-----------------|---------------------------------------|
| Forward Voltage | V_F | IF=500mA | Max. Initial measurement x 1.2 |
| Radiant Flux | Φ_e | IF=500mA | Min. Initial measurement x 0.7 |

Notes :

1. The value is measured after the test sample is cooled down to the room temperature.

Precaution for use

1) Storage

- To avoid moisture penetration, we recommend storing UV LEDs in a dry box with a desiccant. The recommended temperature and Relative humidity are between 5℃ and 30℃ and below 50% respectively.
- LEDs must be stored properly to maintain the device. If the LEDs are stored for 3 months or more after being shipped from SVC, a sealed container with a nitrogen atmosphere should be used for storage.
- Replace the remained LEDs into the moisture-proof bag and reseal the bag after work to avoid those LEDs being exposed to moisture. Prolonged exposure to moisture can adversely affect the proper functioning of the LEDs.
- If the package has been opened more than 4 eek(MSL_2a) or the color of the desiccant changes, components should be dried for 10-12hr at 60±5℃
- The conditions of resealing are as follows
 - Temperature is 5 to 40℃ and Relative humidity is less than 30%

2) Handling Precautions

- VOCs (Volatile organic compounds) emitted from materials used in the construction of fixtures can penetrate silicone encapsulants of LEDs and discolor them when exposed to heat and photonic energy. The result can be a significant loss of light output from the fixture. Knowledge of the properties of the materials selected to be used in the construction of fixtures can help prevent these issues.
- In case of attaching LEDs, do not use adhesives that outgas organic vapor.
- Soldering should be done as soon as possible after opening the moisture-proof bag.
- Do not rapidly cool device after soldering.
- Do not apply mechanical force or excess vibration during the cooling process to normal temperature after soldering.
- Components should not be mounted on warped (non coplanar) portion of PCB.
- The UV LED is encapsulated with a silicone resin for the highest flux efficiency. So it needs to be handled carefully as below
 - Avoid touching silicone resin parts especially with sharp tools such as pincettes(Tweezers)
 - Avoid leaving fingerprints on silicone resin parts.
 - Silicone resin will attract dust so use covered containers for storage.
 - When populating boards in SMT production, there are basically no restrictions regarding the form of the pick and place nozzle, except that excessive mechanical pressure on the surface of the resin must be prevented.
 - It is not recommend to cover the silicone resin of the LEDs with other resin (epoxy, urethane, etc).

3) Safety for eyes and skin



- The Products emit high intensity ultraviolet light which can make your eyes and skin harmful, So do not look directly into the UV light and wear protective equipment during operation.

4) Cleaning

- This device is not allowed to be used in any type of fluid such as water, oil, organic solvent , etc.

5) Others

- The appearance and specifications of the product may be modified for improvement without notice.
- When the LEDs are in operation the maximum current should be decided after measuring the package temperature.
- The driving circuit must be designed to allow forward voltage only when it is ON or OFF. If the reverse voltage is applied to LED, migration can be generated resulting in LED damage.
- Do not handle this product with acid or sulfur material in sealed space.

| | |
|---|--|
|  |  CAUTION |
| | <ul style="list-style-type: none"> •UV LEDs emit high intensity UV light. •Do not look directly into the UV light during operation. This can be harmful to your eyes and skin. •Wear protective eyewear to avoid exposure to UV light. •Attach caution labels to your products which contain UV LEDs. <p>Avoid direct eye and skin exposure to UV light. Keep out of reach of children.</p> |

Revision history

| REV | Change Date | Brief summary of change |
|-----|-------------------|-------------------------|
| 00 | November 20, 2013 | Initial specification |
| 01 | February 21, 2014 | Data upgrade |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |